

AMENDMENTS TO THE CLAIMS

The claims below replace all prior versions, and listings, of claims in this application.

1. (Currently Amended) A method for improving the performance of a decoder, comprising:
 - determining an energy value for a transmission from a first station to a second station, the decoder residing in the second station;
 - forming a message carrying an indicator of the energy value, ~~[[the]] an identity of [[the]]~~ a target destination of the payload data a data payload, [[the]] a transmission rate of [[the]] a subpacket, a and the number of subpackets to carry [[the]] a full amount of the data payload, and a timing of the arrival of the subpackets; and
 - transmitting the message to the second station,
 - wherein the energy value is a traffic-to-pilot ratio and (1) determining an energy value includes locating the energy value in a look-up table and selecting an index value associated with the energy value, and (2) forming a message carrying an indicator of the energy value includes forming a message including the index value.
2. (Original) The method of Claim 1, wherein the step of transmitting the message comprises positioning the message in a preamble.
3. (Original) The method of Claim 1, wherein the step of transmitting the message comprises positioning the message in a subpacket.
4. (Original) The method of Claim 1, wherein the step of transmitting the message comprises positioning the message between a preamble and a subpacket.
5. (Cancelled).

6. (Original) The method of Claim 1, wherein the first station is a base station and the second station is a remote station.

7. (Currently Amended) The method of Claim 1, wherein the first station is a remote station and the second station is a base station.

8. (Currently Amended) An apparatus for improving the performance of a decoder, comprising:

means for determining an energy value for a transmission from a first station to a second station, the decoder residing in the second station;

means for forming a message carrying an indicator of the energy value, ~~[[the]]~~ an identity of ~~[[the]]~~ a target destination of ~~the payload data~~ a data payload, ~~[[the]]~~ a transmission rate of ~~[[the]]~~ a subpacket, ~~a~~ and the number of subpackets to carry ~~[[the]]~~ a full amount of the data payload, and a timing of the arrival of the subpackets; and

means for transmitting the message to the second station,

wherein the energy value is a traffic-to-pilot ratio and (1) the means for determining an energy value locates the energy value in a look-up table and selects an index value associated with the energy value, and (2) the means for forming a message carrying an indicator of the energy value forms a message including the index value.

9. (Currently Amended) A computer-readable media including computer-readable instructions thereon for performing the steps of:

determining an energy value for a transmission from a first station to a second station, a decoder residing in the second station;

forming a message carrying an indicator of the energy value, ~~[[the]]~~ an identity of ~~[[the]]~~ a target destination of ~~the payload data~~ a data payload, ~~[[the]]~~ a transmission rate of ~~[[the]]~~ a subpacket, ~~a~~ and the number of subpackets to carry ~~[[the]]~~ a full amount of the data payload, and a timing of the arrival of the subpackets; and

transmitting the message to the second station,

wherein the energy value is a traffic-to-pilot ratio and (1) the step of determining an energy value includes locating the energy value in a look-up table and selecting an index value associated with the energy value, and (2) the step of forming a message carrying an indicator of the energy value includes forming a message including the index value.

10. (Currently Amended) An apparatus for improving the performance of a decoder, comprising:

a transmission power control unit for determining an energy value for a transmission from a first station to a second station, the decoder residing in the second station; and

a channel element coupled to the transmission power control unit for forming a message carrying an indicator of the energy value, ~~[[the]]~~ an identity of ~~[[the]]~~ a target destination of ~~the~~ payload data a data payload, ~~[[the]]~~ a transmission rate of ~~[[the]]~~ a subpacket, a ~~and the number~~ of subpackets to carry ~~[[the]]~~ a full amount of the data payload, and a timing of the arrival of the subpackets and for transmitting the message to the second station,

wherein the energy value is a traffic-to-pilot ratio and (1) determining an energy value includes locating the energy value in a look-up table and selecting an index value associated with the energy value, and (2) forming a message carrying an indicator of the energy value includes forming a message including the index value.

11. (Previously Presented) The apparatus of Claim 10, wherein the transmitting the message comprises positioning the message in a preamble.

12. (Previously Presented) The apparatus of Claim 10, wherein the transmitting the message comprises positioning the message in a subpacket.

13. (Previously Presented) The apparatus of Claim 10, wherein the transmitting the message comprises positioning the message between a preamble and a subpacket.

14. (Cancelled).

15. (Previously Presented) The apparatus of Claim 10, wherein the first station is a base station and the second station is a remote station.

16. (Currently Amended) The apparatus of Claim 10, wherein the first station is a remote station and the second station is a base station.

17. (Currently Amended) A base station for improving the performance of a decoder, comprising:

a transmission power control unit for determining an energy value for a transmission from a first station to a second station, the decoder residing in the second station;

a channel element coupled to the transmission power control unit for forming a message carrying an indicator of the energy value, ~~[[the]]~~ an identity of ~~[[the]]~~ a target destination of ~~the~~ payload data a data payload, ~~[[the]]~~ a transmission rate of ~~[[the]]~~ a subpacket, a ~~and the~~ number of subpackets to carry ~~[[the]]~~ a full amount of the data payload, and a timing of the arrival of the subpackets; and

a transmitter adapted to transmit the message in a forward link channel to the remote stations,

wherein the energy value is a traffic-to-pilot ratio and (1) determining an energy value includes locating the energy value in a look-up table and selecting an index value associated with the energy value, and (2) forming a message carrying an indicator of the energy value includes forming a message including the index value.

18. (Currently Amended) A remote station for improving the performance of a decoder, comprising:

a transmission power control unit for determining an energy value for a transmission to a base station, the decoder residing in the base station;

a channel element coupled to the transmission power control unit for forming a message carrying an indicator of the energy value, ~~[[the]]~~ an identity of ~~[[the]]~~ a target destination of ~~the~~ payload data a data payload, ~~[[the]]~~ a transmission rate of ~~[[the]]~~ a subpacket, a ~~and the~~ number

of subpackets to carry [[the]] a full amount of the data payload, and a timing of the arrival of the subpackets; and

a transmitter adapted to transmit the message in a reverse link channel to the base station, wherein the energy value is a traffic-to-pilot ratio and (1) determining an energy value includes locating the energy value in a look-up table and selecting an index value associated with the energy value, and (2) forming a message carrying an indicator of the energy value includes forming a message including the index value.